



## STARTPLEX

**Okoume face veneers II/III**  
**Exterior gluing Class 3 - E1**  
**NF Extérieur CTB-X certified (for structural use)**

Okoume faced twin panel for non exposed outdoor use.  
 Common outdoor applications without any direct or prolonged exposure (many applications on work sites).



## TECHNICAL INFORMATION

### GENERAL INFORMATION

**Compliance of plywood with European norms:**

- Gluing class: according to EN 314-2
- Faces classification: according to EN 635-2
- Dimension tolerance: according to EN 315
- Panel marking: according to EN 636-3

### SPECIFICATIONS

Thicknesses: 5 to 40 mm.

**CE2+** marking for structural use (according to EN 13986) for panels with a thickness  $\geq 8$  mm (control certificate delivered by FCBA).

**CE NS** marking for non-structural use (according to EN 13986) for panels with a thickness  $< 8$  mm.

Density:	475 kg/m <sup>3</sup> ( $\pm 50$ kg/m <sup>3</sup> )
Fire reaction:	D-s2, d0 for thicknesses $\geq 10$ mm* E for thicknesses $< 10$ mm*
Formaldehyde emission:	Class E1 US EPA TSCA Title VI - CARB ULEF
Heat conductivity:	$\lambda = 0,13$ W/m.k
Pentachlorophenol content:	$< 5$ ppm

\* Depending on how the panel is installed.

Thickness mm	Sizes cm
5	250 x 122
8	310 x 153
10	
12	
15	
18	
20	
22	
25	
30	
40	

For PEFC™-certified panels, depending on available credits, contact us.